

Vaisala Veriteq Temperature Data Recorder Series 1000/1400



Features/Benefits

- Industry-leading precision and accuracy
- Adjustable time based recording
- Printed reports for any time period
- Extended long-life 10-year battery
- Validation and continuous monitoring with the same model
- Two year limited warranty
- Superior alternative to chart recorders and hard-wired systems
- NIST-traceable, A2LA accredited calibration
- Timebase calibrated over the operating temperature range
- Snap-in logger cradle for easy network connectivity

The 1000/1400 series temperature data recorders include the VL-series for regulated environments and the SP-series for non FDA/GxP industries.

The VL-series of data recorders, together with vLog software provide a superior, high accuracy solution for use in FDA/GxP regulated environments by providing tamper-proof files and encrypted electronic records that meet 21 CFR Part 11 requirements.

The SP-series provides a compact, easily deployable, highly accurate

measurement and recording device for use in non FDA/GxP regulated industries. Coupled with Spectrum software for downloading, displaying, analyzing and reporting of recorded environmental data, the SP-series was designed for use in non FDA/GxP regulated environments.

Optional browser-based viewLinc software provides 24/7 multi-stage alarm notification and remote monitoring for both the VL and SP-series of data recorders.

Technical Data

General

Size	85 x 59 x 26 mm (3.4 x 2.3 x 1") 76 g (2.7oz)
Interfaces	RS-232 serial, USB, Ethernet, WiFi, PoE network interface available
Mounting	Magnetic strips, 3M Dual Lock™ Fasteners Snap-in connector locks provide secure probe connections
PC Software	Graphing & Reporting Software Spectrum for SP-series vLog for VL-series viewLinc for continuous monitoring & alarming OPC Server to add on to existing OPC compatible monitoring systems
Internal Clock	Accuracy ±1 min./month -25 °C to +70 °C (-13 °F to +158 °F)
Electromagnetic Compatibility	FCC Part 15 and CE
Power Source	Internal 10-year lithium battery (Battery life specified with sample interval of 1 min. or longer)

Internal Temperature Sensor

Series	Sensor Type
1000-21x, 1000-LT	Precision-tolerance epoxy-encapsulated NTC thermistor

Memory

Data Sample Capacity	
1000-2XX, 1000-LT	48,100 12-bit samples
1400-44X	85,300 12-bit samples
Memory Type	Non-volatile EEROM
Memory Modes	Users-selectable. Wrap (FIFO) or stop when memory is full. User selectable start time. User selectable stop time (VL series only).
Sampling Rates	Users-selectable (in 10 second intervals) from once every 10 seconds to once a day. (Battery life specified with sample interval of 1 min. or longer)

Recording Span: 1000-2xx

SAMPLE INTERVAL	NUMBER OF CHANNELS ENABLED	
	1	2
10 Seconds	5.5 Days	2.7 Days
1 Minute	1.1 Months	16.7 Days
5 Minutes	5.5 Months	2.7 Months
15 Minutes	1.3 Years	8.3 Months
1 Hour	5.4 Years	2.7 Years



VL-1000-21x



VL-1000-22x

Recording Span: 1400-44x

SAMPLE INTERVAL	NUMBER OF CHANNELS ENABLED			
	1	2	3	4
10 Seconds	9.8 Days	4.9 Days	3.2 Days	2.4 Days
1 Minute	1.9 Months	29.6 Days	19.7 Days	14.8 Days
5 Minutes	9.8 Months	4.9 Months	3.2 Months	2.4 Months
15 Minutes	2.4 Years	1.2 Years	9.8 Months	7.4 Months
1 Hour	9.7 Years	4.8 Years	3.2 Years	2.4 Years



VL-1400-44x

EPT Series Temperature Probes

EPT-23N-XXN SERIES

Sensor	"N" Range External Probe
Operation Range	-40 °C to +95 °C (-40 °F to +203 °F)
Connector Color Code	Black
Sensor Tip	Stainless Steel, Diameter: 3.2 mm (1/8") Length: 38 mm (1.5")
Probe Length	"xx" denotes the length of the probe in feet. 3 m (10') and 7.6 m (25') lengths available
Cable Construction	2 mm (0.07") Diameter, Teflon coated cable

EPT-23N-XXL SERIES

Sensor	"L" Range External Probe
Operation Range	-60 °C to +95 °C (-76 °F to +203 °F)
Connector Color Code	Green
Sensor Tip	Stainless Steel, Diameter: 3.2 mm (1/8") Length: 38 mm (1.5")
Probe Length	"xx" denotes the length of the probe in feet. 3 m (10') and 7.6 m (25') lengths available
Cable Construction	2 mm (0.07") Diameter, Teflon coated cable

EPT-23N-XXV SERIES

Sensor	"V" Range External Probe
Operating Range	-95 °C to +95 °C (-139 °F to +203 °F)
Connector Color Code	Blue
Sensor Tip	Stainless Steel, Diameter: 3.2 mm (1/8") Length: 38 mm (1.5")
Probe Length	"xx" denotes the length of the probe in feet. 3 m (10') and 7.6 m (25') lengths available
Cable Construction	2 mm (0.07") Diameter, Teflon coated cable

EPT-22W-10N SERIES

Sensor	"N" Range External Probe
Operation Range	-40 °C to +95 °C (-40 °F to +203 °F)
Connector Color Code	Black
Sensor Tip	Sealed Teflon Tip Diameter: 3 mm (0.12") Length: 28 mm (1.1")
Probe Length	3 m (10')
Cable Construction	2 mm (0.07") Diameter, Teflon coated cable

Liquid Submersible Probe

EPT-22W-10L SERIES

Sensor	"L" Range External Probe
Operation Range	-60 °C to +95 °C (-76 °F to +203 °F)
Connector Color Code	Green
Sensor Tip	Sealed Teflon Tip Diameter: 3 mm (0.12") Length: 28 mm (1.1")
Probe Length	3 m (10')
Cable Construction	2 mm (0.07") Diameter, Teflon coated cable

Liquid Submersible Probe

Temperature Probe Accessories

Thermal Dampening Block, for use in refrigerators and freezers, simulates a glycol bottle to reduce viewLinc alarms generated by opening and closing a door.



Product Part Number Legend: Guide for reading the product tables and selecting the most appropriate model for your application.

XX - 1000 - XXX

Series Type: VL (Validatable) or SP

Series Number: Series 1000: 2 Channel,
Series 1400: 4 Channel

Total Number of Channels: 2/4

Number of External Channels: 1/2/4

External Channel Temperature Range:

Please refer to the Temperature Range and Accuracy table below for external probe options.

Temperature Range and Accuracy 1000-LT Series

INTERNAL SENSOR	
Calibrated	-40 °C to +40 °C (-40 °F to +104 °F)
Measurement Range	
Storage Range	-40 °C to +85 °C (-40 °F to +185 °F)
Initial Accuracy*	+/-0.25 °C over -40 °C to +40 °C (+/-0.45 °F over -40 °F to +40 °F)
One Year Accuracy*	+/-0.5 °C over -40 °C to +40 °C (+/-0.9 °F over -40 °F to +40 °F)
Resolution	0.02 °C at 0 °C (0.04 °F at +32 °F)
"L" RANGE EXTERNAL PROBE	
Calibrated	-40 °C to +40 °C (-40 °F to +104 °F)
Measurement Range	
Storage Range	-60 °C to +95 °C (-76 °F to +203 °F)
Initial Accuracy*	+/-0.25 °C over -40 °C to +40 °C (+/-0.45 °F over -40 °F to +40 °F)
One Year Accuracy*	+/-0.5 °C over -40 °C to +40 °C (+/-0.9 °F over -40 °F to +40 °F)
Resolution	0.02 °C at 0 °C (0.04 °F at +32 °F)

*Specification for external channels is for a probe calibrated to the specific channel of the data logger and with the data logger at -25 °C to +70 °C (-13 °F to +122 °F)

Temperature Range and Accuracy 1000-2XX and 1400-44X Series

INTERNAL SENSOR	
Calibrated	-25 °C to +70 °C (-13 °F to +158 °F)
Measurement Range	
Storage Range	-40 °C to +85 °C (-40 °F to +185 °F)
Initial Accuracy*	0 %RH to 100 %RH non-condensing +/-0.10 °C over +20 °C to +30 °C (+/-0.18 °F over +68 °F to +86 °F) +/-0.15 °C over -25 °C to +70 °C (+/-0.27 °F over -13 °F to +158 °F)
One Year Accuracy*	+/-0.15 °C over +20 °C to +30 °C (+/-0.27 °F over +68 °F to +86 °F) +/-0.25 °C over -25 °C to +70 °C (+/-0.45 °F over -13 °F to +158 °F)
Resolution	0.02 °C at +25 °C (0.04 °F at +77 °F)
"N" RANGE EXTERNAL PROBE	
Calibrated	-25 °C to +70 °C (-13 °F to +158 °F)
Measurement Range	
Storage Range	-40 °C to +95 °C (-40 °F to +203 °F)
Initial Accuracy*	+/-0.10 °C over +20 °C to +30 °C (+/-0.18 °F over +68 °F to +86 °F) +/-0.15 °C over -25 °C to +70 °C (+/-0.27 °F over -13 °F to +158 °F)
One Year Accuracy*	+/-0.15 °C over +20 °C to +30 °C (+/-0.27 °F over +68 °F to +86 °F) +/-0.25 °C over -25 °C to +70 °C (+/-0.45 °F over -13 °F to +158 °F)
Resolution	0.02 °C at +25 °C (0.04 °F at +77 °F)
"L" RANGE EXTERNAL PROBE	
Calibrated	-50 °C to +10 °C (-58 °F to +50 °F)
Measurement Range	
Storage Range	-60 °C to +95 °C (-76 °F to +203 °F)
Initial Accuracy*	+/-0.15 °C over -50 °C to +10 °C (+/-0.27 °F over -58 °F to +50 °F)
One Year Accuracy*	+/-0.25 °C over -50 °C to +10 °C (+/-0.45 °F over -58 °F to +50 °F)
Resolution	0.02 °C at -20 °C (0.04 °F at -4 °F)
"V" RANGE EXTERNAL PROBE	
Calibrated	-90 °C to -40 °C (-130 °F to -40 °F)
Measurement Range	
Storage Range	-95 °C to +95 °C (-139 °F to +203 °F)
Initial Accuracy*	+/-0.15 °C over -90 °C to -40 °C (+/-0.27 °F over -130 °F to -40 °F)
One Year Accuracy*	+/-0.25 °C over -90 °C to -40 °C (+/-0.45 °F over -130 °F to -40 °F)
Resolution	0.02 °C at -80 °C (0.04 °F at -112 °F)



For more information, visit www.vaisala.com or contact us at sales@vaisala.com

Ref. B211044EN-A ©Vaisala 2010
This material is subject to copyright protection, with all copyrights retained by Vaisala and its individual partners. All rights reserved. Any logos and/or product names are trademarks of Vaisala or its individual partners. The reproduction, transfer, distribution or storage of information contained in this brochure in any form without the prior written consent of Vaisala is strictly prohibited. All specifications — technical included — are subject to change without notice.

